



DI PRIMER ACR

Deep Impregnating Primer

DESCRIPTION

DI PRIMER is an acrylic modified product, which has deep impregnating action on porous substrates. On application it gives a clear film over the substrate thereby binding all loose particles.

ADVANTAGES

DI PRIMER, having a deep impregnating action, gives bonding from within the surface hence the result for topcoats are very good. It also helps seal all the dust particles on the surface, which again results in better bonding between surface and topcoats.

RECOMMENDED USES

- Can be used as a primer coat under all waterproof coatings system.
- Can be used as a sealer to seal porous substrates like concrete, sand stone etc.

COVERAGE

1 Lt. DI PRIMER will cover approximately 6 – 7-sqmt areas in one coat application.

SURFACE PREPARATION

The surface must be clean and rough. All oil, dirt, debris, paint and unsound concrete must be removed. The final step of cleaning should be complete removal of all residues with a vacuum cleaner or by pressure washing.

METHOD OF APPLICATION

Apply one coat of DI PRIMER over the prepared surface using a brush. if the surface is very porous two coats could be applied with a gap of 2-3 hours between each coat.

SAFETY

DI PRIMER is safe, non-toxic, and eco-friendly and presents no health hazard. As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles

INHALATION: Inhalation of vapor or mist should be avoided. Symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency

EYE CONTACT: Flush eyes with water for 15 minutes and call for medical help.

INGESTION: causes nausea, vomiting, and loss of consciousness. If accidentally swallowed do not induce

SKIN CONTACT: Flush with water or soap and water until all traces have been removed. Seek medical attention if required.

STORAGE

Minimum 18 months in unopened container. Store away from sunlight and preferably below 30°C.

PACKING

DI PRIMER is packaged in 20 ltr containers.

Technical Support:



& Polymertech UK Ltd.
CN-07468396
United Kingdom

NOTE:- We make no warranty either expressed or implied or statutory in this document except as expressly stated in any sale and purchase agreement entered into between the buyer and us. This document is a technical data information sheet. The information given in this sheet is to the best of our knowledge, true and accurate. However buyers are requested to confirm the same in their laboratories as test results may vary between two laboratories due to change in test conditions, purity of chemicals and personal error of chemists. Under the above conditions we are not liable for special, incidental or consequential damage.

For further assistance kindly mail us : support@starcoating.in

Marketed By:



Star Coatings & Membranes Pvt. Ltd.

New Delhi-110025, visit us at : www.starcoating.in, E-mail: info@starcoating.in



(ISO 9001:2000)