



ENIROOF CLEAR

CLEAR WATERPROOF COATING

DESCRIPTION

ENIROOF CLEAR is a blend of special resin, Polymer, organic and inorganic compound. It waterproofs the concrete and other absorbent surfaces very effectively. They give glossy finish with enhance the colour of the substrate. It is single pack easy to apply liquid.

ADVANTAGES

- Excellent coating for exterior brick tiles, dhollpur marble and other stones.
- Blocks all the pores, prevent water penetration through capillary action.
- Protective seal prevents stain and dirt penetration.
- Being transparent, cause no changes in colour or look of the substrate.
- Film will not yellow or darken with time.

RECOMMENDED USES

- It is an excellent waterproofer for terraces, roofs, parapet walls, chajjas, exterior and interior walls of buildings etc.
- Water proofing of tiles like mosaic, dholpur, and marble, chips tiles where the aesthetic color value retention is of prime importance.
- For chemical resistance of molasses tanks, storage of mild acids, alkalies in factories or processing houses.
- As an anti corrosive primer for metal surfaces under chassis.
- As an anti corrosive primer for metal surfaces, steel structures, G.I sheets, pipes, machinery.

COVERAGE

The coverage depends on the type of the surface.
First coat ... smooth surface --- 50-60 sqft
Second coat ... smooth surface --- 55-65 sqft

PACKING

ENIROOF CLEAR is Available in 1 gallon & 20 kg pails.

METHOD OF APPLICATION

First of all the surface must be prepared properly. The entire surface must be clean, free from dirt, grease, oil and other loose particles. Fill the visible cracks, joints and gaps with crack filler. Allow it to cure for 24 hrs. , Observe the filled area, if required fill the cracks once again to the level of the surface. Mix the container well and apply one coat of **ENIROOF CLEAR** on the prepared surface, allow it to dry for 4-6 hours. Apply the 2nd coat of **ENIROOF CLEAR**. If subsequent coats are required then apply at an interval of 6 hours. It is recommended to apply **ENIROOF CLEAR** on a bone-dry surface. Paint can be applied as a topcoat over **ENIROOF CLEAR** coating directly.

SAFETY

Being inflammable, it should be stored in a cool dry place away from heat and naked flames. Working areas should be ventilated. Smoking should not be permitted during application.

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles

INHALATION: Inhalation of vapor or mist should be avoided. Symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency

EYE CONTACT: Flush eyes with water for 15 minutes and call for medical help.

INGESTION: causes nausea, vomiting, and loss of consciousness. If accidentally swallowed do not induce

SKIN CONTACT: Flush with water or soap and water until all traces have been removed. Seek medical attention if required.

STORAGE

Minimum 18 months in unopened container. Store away from sunlight and preferably below 30°C.

Technical Support:



& Polymertech UK Ltd.
CN-07468396
United Kingdom

NOTE:- We make no warranty either expressed or implied or statutory in this document except as expressly stated in any sale and purchase agreement entered into between the buyer and us. This document is a technical data information sheet. The information given in this sheet is to the best of our knowledge, true and accurate. However buyers are requested to confirm the same in their laboratories as test results may vary between two laboratories due to change in test conditions, purity of chemicals and personal error of chemists. Under the above conditions we are not liable for special, incidental or consequential damage.

For further assistance kindly mail us : support@starcoating.in

Marketed By:



Star Coatings & Membranes Pvt. Ltd.

New Delhi-110025, visit us at : www.starcoating.in, E-mail: info@starcoating.in



(ISO 9001:2000)